



Nominal pressure		PN16
Test pressure	Strength test	2.4Mpa
	Sealing test	1.76Mpa
Maximum working temperature		-10°C to +90°C
Suitable Media		W.O.G etc

- 1.Design and manufacture according to API609.
- 2.Face to face according to DIN3202-K1.
- 3.Flange drilling according to AS4087 PN16
- 4.Top flange drilling according to ISO 5211.
- 5.Pressure test according to ISO5208.

Size	L	AS4087 PN16		Øc	H1	H2	H3	ØE	Ø E1
		ØD1	n- Ød1						
DN700	165	845	20-30	63.35	623.9	505.1	66	300	254
DN800	190	984	20-36	63.35	672	576	66	300	254
DN900	203	1092	24-36	75	720	637	118	300	254
DN1000	216	1175	24-36	85	800	701	142	300	254
DN1200	276	1410	32-36	105	940	844	160	350	298

7	Pin	Stainless Steel			
6	Seat	EPDM			
5	Disc	SS304			
4	Stem	SS416			
3	O Ring	NBR			
2	Bushing	PTFE			
1	Body	GGG40			
Item	Part name	material		q'ty	remark
DRN	Wang	WEIGHT		MATERIAL	
CHK		SCALE		Butterfly Valve	
APP		DATE	06/15/2015		
hiwa				B10W-YX	
				REV	20150615

This document is the property of Huihua Valve Industry Co.
 Distribution of this document without the written consent of the owner is strictly forbidden
 Failure to comply will incur a liability for damages

<http://www.hiwa.cn> Website
 sales@hiwa.cn Email

86 - 533 - 6077200 Phone
 86 - 533 - 6077233 FAX

Huihua Valve Industry co.
 No.36 MinAn Road New Hi-Tech Industry
 Zone Zibo Shandong China 255088 p.c