



- 1.Design conforms to AS2638.2 .
- 2.Face to Face according to AS2638.2.
- 3.Flanges standard AS4087 PN16.
- 4.Pressure test according to AS2638.2.

DN	L	D	D1	D2	b	f	n-d	H	W
50	178	150	114	90	18	3	4-18	270	180
65	190	165	127	103	18	3	4-18	280	180
80	203	185	146	122	18	3	4-18	290	200
100	229	215	178	154	20	3	4-18	315	200
150	267	280	235	211	23	3	8-18	410	280
200	292	335	292	268	23	3	8-18	515	320
225	330	405	324	300	24	3	8-18	560	320
250	330	405	356	328	24	3	8-22	605	320
300	356	455	406	378	30	4	12-22	695	450
350	381	525	470	438	33	4	12-26	790	450
375	406	580	495	463	33	4	12-26	880	450
400	406	580	521	489	33	4	12-26	970	560
450	432	640	584	552	33	4	12-26	1045	560
500	457	705	641	609	35	4	16-26	1120	800
600	508	825	756	720	42	5	16-30	1320	800

14	Handwheel	AS 1831 500-7		
13	Dust Guard	NBR/EPDM		
12	O-Ring	NBR/EPDM		
11	O-Ring	NBR/EPDM		
10	Bushing Nut	Brass		
9	Washer	Nylon		
8	Up sealing	NBR/EPDM		
7	Bonnet	AS 1831 500-7		
6	Bolt	Zinc plated steel		
5	Bonnet Gasket	EPDM		
4	Stem Nut	Brass		
3	Stem	SS410		
2	Wedge	AS 1831 500-7 +EPDM		
1	Body	AS 1831 500-7		
No.	Part	Material		

DRN	Wang	WEIGHT		MATERIAL
CHK		SCALE		Gate Valve
APP		DATE	11/11/2013	

hiwa

REV 20131111